

SODA FAST

FOUNTAIN EQUIPMENT
Remote Fountain Chillers

R290

Discover a complete range of essential products for a top-notch fountain system at ICI

LF-R

POST-MIX FOUNTAIN CHILLER





Qty	Part
☐	LF-R-0 Carbonated & non-carb (0 syrup coils)
☐	LF-R-1 Carbonated & non-carb (1 syrup coils)
☐	LF-R-2 Carbonated & non-carb (2 syrup coils)
☐	LF-R-3 Carbonated & non-carb (3 syrup coils)
☐	LF-R-4 Carbonated & non-carb (4 syrup coils)
☐	LF-R-5 Carbonated & non-carb (5 syrup coils)
☐	LF-R-6 Carbonated & non-carb (6 syrup coils)

Features:

- Self-contained, remote, cold carb chiller, for post mix dispenser towers or bar guns
- Mechanical refrigeration with 4-gallon water bath & 9.5 lb. ice bank
- Carbonator tank, water and syrup coils submerged in water bath to achieve optimum dispense temperature
- Available with up to 6 syrup coils (carbonated and non-carb)
- Rated for 1-1/2 twelve-ounce drinks per minute (<40°F with an influent water temperature of <75°F)
- ETL and NSF Listed
- Made in the USA
- 8ft NEMA 5-15P power cord

LF-R SODA FAST FOUNTAIN CHILLER



Chiller horse power	1/5 H.P.
Voltage/phase/amps	120/1/10.3
Refrigerant	R290
Refrigeration ampacity	3
Carb pump amps	6.5
Agitator pump amps	0.8
Height	24.5"
Depth	23.5"
Width	12.25"
Ship weight	150 lbs
Dry weight	115 lbs
Draw rate	1½-12oz/min
Water bath	4 gal
Ice bank	9.5 lbs

ACCESSORIES:

- ☐ 24PL/H1L3U8B13: Primary CO2 regulator, high-pressure 160 PSI 1/4" flare with check valve, nylon flare and cylinder washer
- ☐ CR-CWB1: Single cylinder wall bracket to safely strap and secure cylinders to the wall
- ☐ CR-CWB2: Two cylinders wall bracket to safely strap and secure cylinders to the wall
- ☐ CR-CTAC2: CO2 cylinder auto change over device. Connects two cylinders at one time to double your CO2 capacity
- ☐ CR-24FCP: Twin filter system with prefilter, with compact fibredyne filters, 19"H x 17"W 5 gpm, 30,000 gal, TOC & 1/2 micron filtration
- ☐ CR-24FC: Twin filter system without prefilter, with compact fibredyne filters, 19"H x 17"W 5 gpm, 30,000 gal, TOC & 1/2 micron filtration
- ☐ BIB-RACK 4FL: Backroom kit, 4 BIB pumps, two wide by two high flat shelves
- ☐ BIB-RACK 6FL: Backroom kit, 6 BIB pumps, two wide by two high flat shelves
- ☐ WMB1: Chiller Wall Mounting Bracket
- ☐ S1318-SET: Low profile, adjustable glide feet

Beverage systems for every application and use.

16630 Koala Rd, Adelanto, CA 92301 | (800) 854-1177 | ici.us

ICI INTERNATIONAL
CARBONIC INC.

Rev. 09252025